



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



**FRANZEF OSS
MINERALS**

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Substance name: QL-100-AF

Synonyms: Lime, Burnt lime, Un-slaked lime, Building lime, Calcia, Fat lime, Chemical lime, Fluxing lime, Hard burnt lime, Soft burnt lime, Pebble lime, Calcium oxide, Calcium monoxide, Quick lime, Calcined limestone.

Chemical name and formula: Calcium oxide – CaO

CAS: 1305-78-8
EINECS: 215-138-9
Molecular Weight: 56.08 g/mol
REACH Registration number: 01-2119475325-36-0043

1.2 Relevant identified uses of the substance or mixture and uses advised against

Please check the identified uses in table 1 of the Appendix of this SDS.

Uses advises against: There are no uses advised against.

1.3 Details of the supplier of the safety data sheet

Name: **Franzefoss Minerals AS**
Address: **Olav Ingstadsvei 5, 1309 Rud, Norway**
Phone N°: **+47 975 05 255**
Fax N°: **-**
E-mail of competent person responsible for SDS in the MS or in the EU: **post@kalk.no, jan.olav.ryan@kalk.no**

1.4 Emergency telephone number

European Emergency N°: 112

National centre for Prevention and Treatment of Intoxications N°: **Helsedirektoratet, Giftinformasjonen, Pb. 7000 St. Olavs plass, 0130 Oslo, Norway, e.mail: giftinfo@helsedir.no, Phone: +47 22 59 13 00**

Emergency telephone at the company **+47 975 05 255**

Available outside office hours: Yes No



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



FRANZEFOSS
MINERALS

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance

2.1.1 Classification according to Regulation (EC) 1272/2008

STOT Single Exp. 3, Route of exposure: Inhalation

Skin Irritation 2

Eye Damage 1

2.2 Label elements

2.2.1 Labelling according to Regulation (EC) 1272/2008

Signal word: Danger

Hazard pictogram:



Hazard statements:

H315: Causes skin irritation
H318: Causes serious eye damage
H335: May cause respiratory irritation

Precautionary statements:

P102: Keep out of reach of children
P280: Wear protective gloves/protective clothing/eye protection/face protection
P305+P351+P310: IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTRE or doctor/physician
P302+P352: IF ON SKIN: Wash with plenty of water
P261: Avoid breathing dust/spray
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P501: Dispose of contents/container in accordance with local/regional/national/international regulation : FOR 2004-06-01 nr. 930: Forskrift om gjenvinning og behandling av avfall (avfallsforskriften) Kap 11. Inkludert den europeiske avfallslisten. Avfall fra letting, utvinning og i steinbrudd og fysisk og kjemisk behandling av mineraler: EAL- kode 010407, 010305

2.3 Other hazards

The substance does not meet the criteria for PBT or vPvB substance.
No other hazards identified.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



**FRANZEFOSS
MINERALS**

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Main constituent

Name:	Calcium oxide
CAS:	1305-78-8
EINECS:	215-138-9

Impurities

No impurities relevant for classification and labelling.

4 FIRST AID MEASURES

4.1 Description of first aid measures

General advice

No known delayed effects. Consult a physician for all exposures except for minor instances.

Following inhalation

Move source of dust or move person to fresh air. Obtain medical attention immediately.

Following skin contact

Carefully and gently brush the contaminated body surfaces in order to remove all traces of product. Wash affected area immediately with plenty of water. Remove contaminated clothing. If necessary seek medical advice.

Following eye contact

Rinse eyes immediately with plenty of water and seek medical advice.

Following ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Calcium oxide is not acutely toxic via the oral, dermal, or inhalation route. The substance is classified as irritating to skin and the respiratory tract, and entails a risk of serious damage to the eye. There is no concern for adverse systemic effects because local effects (pH-effect) are the major health hazard.

4.3 Indication of any immediate medical attention and special treatment needed

Follow the advises given in section 4.1

5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

5.1.1 Suitable extinguishing media

Suitable extinguishing media: The product is not combustible. Use a dry powder, foam or CO₂ fire extinguisher to extinguish the surrounding fire.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.1.2 Unsuitable extinguishing media

Do not use water. Avoid humidification.

5.2 Special hazards arising from the substance or mixture

Calcium oxide reacts with water and generates heat. This may cause risk to flammable material.

5.3 Advice for fire fighters

Avoid generation of dust. Use breathing apparatus. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation.

Keep dust levels to a minimum.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8).

Avoid humidification.

6.1.2 For emergency responders

Keep dust levels to a minimum.

Ensure adequate ventilation.

Keep unprotected persons away.

Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8).

Avoid inhalation of dust – ensure that sufficient ventilation or suitable respiratory protective equipment is used, wear suitable protective equipment (see section 8).

Avoid humidification.

6.2 Environmental precautions

Contain the spillage. Keep the material dry if possible. Cover area if possible to avoid unnecessary dust hazard. Avoid uncontrolled spills to watercourses and drains (pH increase). Any large spillage into watercourses must be alerted to the Environment Agency or other regulatory body.

6.3 Methods and material for containment and cleaning up

In all cases avoid dust formation.

Keep the material dry if possible.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



FRANZEFOSS
MINERALS

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

Pick up the product mechanically in a dry way.

Use vacuum suction unit, or shovel into bags.

6.4 Reference to other sections

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13 and the Annex of this safety data sheet.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

7.1.1 Protective measures

Avoid contact with skin and eyes. Wear protective equipment (refer to section 8 of this safety data sheet). Do not wear contact lenses when handling this product. It is also advisable to have individual pocket eyewash. Keep dust levels to a minimum. Minimize dust generation. Enclose dust sources, use exhaust ventilation (dust collector at handling points). Handling systems should preferably be enclosed. When handling bags usual precautions should be paid to the risks outlined in the Council Directive 90/269/EEC.

7.1.2 Advice on general occupational hygiene

Avoid inhalation or ingestion and contact with skin and eyes. General occupational hygiene measures are required to ensure safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no drinking, eating and smoking at the workplace. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home.

7.2 Conditions for safe storage, including any incompatibilities

The substance should be stored under dry conditions. Any contact with air and moisture should be avoided. Bulk storage should be in purpose – designed silos. Keep away from acids, significant quantities of paper, straw, and nitro compounds. Keep out of reach of children. Do not use aluminium for transport or storage if there is a risk of contact with water.

7.3 Specific end use(s)

Please check the identified uses in table 1 of the Appendix of this SDS.

For more information please see the relevant exposure scenario, available via your supplier/given in the Appendix, and check section 2.1: Control of worker exposure.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

SCOEL recommendation (SCOEL/SUM/137 February 2008; see Section 16.6):

Occupational Exposure Limit (OEL), 8 h TWA: 1 mg/m³ respirable dust of calcium oxide

Short-term exposure limit (STEL), 15 min: 4 mg/m³ respirable dust of calcium oxide

PNEC aqua = 370 µg/l



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

PNEC soil/groundwater = 816 mg/l

8.2 Exposure controls

To control potential exposures, generation of dust should be avoided. Further, appropriate protective equipment is recommended. Eye protection equipment (e.g. goggles or visors) must be worn, unless potential contact with the eye can be excluded by the nature and type of application (i.e. closed process). Additionally, face protection, protective clothing and safety shoes are required to be worn as appropriate.

Please check the relevant exposure scenario, given in the Appendix/available via your supplier.

8.2.1 Appropriate engineering controls

If user operations generate dust, use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne dust levels below recommended exposure limits.

8.2.2 Individual protection measures, such as personal protective equipment

8.2.2.1 Eye/face protection

Do not wear contact lenses. For powders, tight fitting goggles with side shields, or wide vision full goggles. It is also advisable to have individual pocket eyewash.

8.2.2.2 Skin protection

Since calcium oxide is classified as irritating to skin, dermal exposure has to be minimised as far as technically feasible. The use of protective gloves (nitrile), protective standard working clothes fully covering skin, full length trousers, long sleeved overalls, with close fittings at openings and shoes resistant to caustics and avoiding dust penetration are required to be worn.

8.2.2.3 Respiratory protection

Local ventilation to keep levels below established threshold values is recommended. A suitable particle filter mask is recommended, depending on the expected exposure levels - please check the relevant exposure scenario, given in the Appendix/available via your supplier.

8.2.2.4 Thermal hazards

The substance does not represent a thermal hazard, thus special consideration is not required.

8.2.3 Environmental exposure controls

All ventilation systems should be filtered before discharge to atmosphere.

Avoid releasing to the environment.

Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority responsible for environmental protection or other regulatory body.

For detailed explanations of the risk management measures that adequately control exposure of the environment to the substance please check the relevant exposure scenario, available via your supplier.

For further detailed information, please check the Appendix of this SDS.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



FRANZEFOSS
MINERALS

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	White or off white (beige) solid material of varying sizes: Lump, granular or fine powder
Odour:	odourless
Odour threshold:	not applicable
pH:	12.3 (saturated solution at 20 °C)
Melting point:	> 450 °C (study result, EU A.1 method)
Boiling point:	not applicable (solid with a melting point > 450 °C)
Flash point:	not applicable (solid with a melting point > 450 °C)
Evaporation rate:	not applicable (solid with a melting point > 450 °C)
Flammability:	non flammable (study result, EU A.10 method)
Explosive limits:	non explosive (void of any chemical structures commonly associated with explosive properties)
Vapour pressure:	not applicable (solid with a melting point > 450 °C)
Vapour density:	not applicable
Relative density:	3.31 (study result, EU A.3 method)
Solubility in water:	1337.6 mg/L (study results, EU A.6 method)
Partition coefficient:	not applicable (inorganic substance)
Auto ignition temperature:	no relative self-ignition temperature below 400 °C (study result, EU A.16 method)
Decomposition temperature:	not applicable
Viscosity:	not applicable (solid with a melting point > 450 °C)
Oxidising properties:	no oxidising properties (Based on the chemical structure, the substance does not contain a surplus of oxygen or any structural groups known to be correlated with a tendency to react exothermally with combustible material)

9.2 Other information

Not available

10 STABILITY AND REACTIVITY

10.1 Reactivity

Calcium oxide reacts exothermically with water to form Calcium dihydroxide.

10.2 Chemical stability

Under normal conditions of use and storage (dry conditions), calcium oxide is stable.

10.3 Possibility of hazardous reactions

Calcium oxide reacts exothermically with acids to form calcium salts.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



Version: 8.0/EN

Revision date: Aug./ 2022


Printing Date: August 12, 2022

10.4 Conditions to avoid

Minimise exposure to air and moisture to avoid degradation.

10.5 Incompatible materials

Calcium oxide reacts exothermically with water to form calcium dihydroxide:



Calcium oxide reacts exothermically with acids to form calcium salts.

Calcium oxide reacts with aluminium and brass in the presence of moisture leading to the production of hydrogen: $\text{CaO} + 2 \text{Al} + 7 \text{H}_2\text{O} \rightarrow \text{Ca(Al(OH)}_4)_2 + 3 \text{H}_2$

10.6 Hazardous decomposition products

None.

Further information: calcium oxide absorbs moisture and carbon dioxide from air to form calcium carbonate, which is a common material in nature.

11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

a. Acute toxicity

Oral $\text{LD}_{50} > 2000 \text{ mg/kg bw}$ (OECD 425, rat)

Dermal $\text{LD}_{50} > 2500 \text{ mg/kg bw}$ (calcium dihydroxide, OECD 402, rabbit); by read across these results are also applicable to calcium oxide, since in contact with moisture calcium hydroxide is formed.

Inhalation no data available

Calcium oxide is not acutely toxic.

Classification for acute toxicity is not warranted.

b. Skin corrosion/irritation

Calcium oxide is irritating to skin (*in vivo*, rabbit).

Based on experimental results, calcium oxide requires classification as irritating to skin [Skin Irrit 2 (H315 – Causes skin irritation)]

c. Serious eye damage/irritation

Calcium oxide entails a risk of serious damage to the eye (eye irritation studies (*in vivo*, rabbit)).

Based on experimental results, calcium oxide requires classification as severely irritating to the eye [Eye Damage 1 (H318 - Causes serious eye damage)].



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



FRANZEFOS
MINERALS

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

d. Respiratory or skin sensitisation

No data available. Calcium oxide is considered not to be a skin sensitiser, based on the nature of the effect (pH shift) and the essential requirement of calcium for human nutrition.

Classification for sensitisation is not warranted.

e. Germ cell mutagenicity

Bacterial reverse mutation assay (Ames test, OECD 471): Negative

In view of the omnipresence and essentiality of Ca and of the physiological non-relevance of any pH shift induced by calcium oxide in aqueous media, CaO is obviously void of any genotoxic potential, including germ cell mutagenicity.

Classification for genotoxicity is not warranted.

f. Carcinogenicity

Calcium (administered as Ca-lactate) is not carcinogenic (experimental result, rat).

The pH effect of calcium oxide does not give rise to a carcinogenic risk.

Human epidemiological data support lack of any carcinogenic potential of calcium oxide.

Classification for carcinogenicity is not warranted.

g. Reproductive toxicity

Calcium (administered as Ca-carbonate) is not toxic to reproduction (experimental result, mouse).

The pH effect does not give rise to a reproductive risk.

Human epidemiological data support lack of any potential for reproductive toxicity of calcium oxide.

Both in animal studies and human clinical studies on various calcium salts no reproductive or developmental effects were detected. Also see the Scientific Committee on Food (Section 16.6).

Thus, calcium oxide is not toxic for reproduction and/or development.

Classification for reproductive toxicity according to regulation (EC) 1272/2008 is not required.

h. STOT-single exposure

From human data it is concluded that CaO is irritating to the respiratory tract.

As summarised and evaluated in the SCOEL recommendation (Anonymous, 2008), based on human data calcium oxide is classified as irritating to the respiratory system [STOT SE 3 (H335 – May cause respiratory irritation)].

i. STOT-repeated exposure

Toxicity of calcium via the oral route is addressed by upper intake levels (UL) for adults determined by the Scientific Committee on Food (SCF), being

UL = 2500 mg/d, corresponding to 36 mg/kg bw/d (70 kg person) for calcium.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



**FRANZEFOSS
MINERALS**

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

Toxicity of CaO via the dermal route is not considered as relevant in view of the anticipated insignificant absorption through skin and due to local irritation as the primary health effect (pH shift).

Toxicity of CaO via inhalation (local effect, irritation of mucous membranes) is addressed by an 8-h TWA determined by the Scientific Committee on Occupational Exposure Limits (SCOEL) of 1 mg/m³ respirable dust (see Section 8.1).

Therefore, classification of CaO for toxicity upon prolonged exposure is not required.

j. Aspiration hazard

Calcium oxide is not known to present an aspiration hazard.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

12.1.1 Acute/Prolonged toxicity to fish

LC₅₀ (96h) for freshwater fish: 50.6 mg/l (calcium dihydroxide)

LC₅₀ (96h) for marine water fish: 457 mg/l (calcium dihydroxide)

12.1.2 Acute/Prolonged toxicity to aquatic invertebrates

EC₅₀ (48h) for freshwater invertebrates: 49.1 mg/l (calcium dihydroxide)

LC₅₀ (96h) for marine water invertebrates: 158 mg/l (calcium dihydroxide)

12.1.3 Acute/Prolonged toxicity to aquatic plants

EC₅₀ (72h) for freshwater algae: 184.57 mg/l (calcium dihydroxide)

NOEC (72h) for freshwater algae: 48 mg/l (calcium dihydroxide)

12.1.4 Toxicity to micro-organisms e.g. bacteria

At high concentration, through the rise of temperature and pH, calcium oxide is used for disinfection of sewage sludges

12.1.5 Chronic toxicity to aquatic organisms

NOEC (14d) for marine water invertebrates: 32 mg/l (calcium dihydroxide)

12.1.6 Toxicity to soil dwelling organisms

EC₁₀/LC₁₀ or NOEC for soil macroorganisms: 2000 mg/kg soil dw (calcium dihydroxide)

EC₁₀/LC₁₀ or NOEC for soil microorganisms: 12000 mg/kg soil dw (calcium dihydroxide)



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



**FRANZEF OSS
MINERALS**

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

12.1.7 Toxicity to terrestrial plants

NOEC (21d) for terrestrial plants: 1080 mg/kg (calcium dihydroxide)

12.1.8 General effect

Acute pH-effect. Although this product is useful to correct water acidity, an excess of more than 1 g/l may be harmful to aquatic life. pH-value of > 12 will rapidly decrease as result of dilution and carbonation

12.1.9 Further information

The results by read across are also applicable to calcium oxide, since in contact with moisture calcium hydroxide is formed

12.2 Persistence and degradability

Not relevant for inorganic substances

12.3 Bioaccumulative potential

Not relevant for inorganic substances

12.4 Mobility in soil

Calcium oxide reacts with water and/or carbon dioxide to form respectively calcium dihydroxide and/or calcium carbonate, which are sparingly soluble, and present a low mobility in most soils.

12.5 Results of PBT and vPvB assessment

Not relevant for inorganic substances

12.6 Other adverse effects

No other adverse effects are identified

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal of calcium oxide should be in accordance with local and national legislation. Processing, use or contamination of this product may change the waste management options. Dispose of container and unused contents in accordance with applicable member state and local requirements.

The used packing is only meant for packing this product; it should not be reused for other purposes. After usage, empty the packing completely.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



FRANZEFOS
MINERALS

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

14 TRANSPORT INFORMATION

Calcium oxide is not classified as hazardous for transport (ADR (Road), RID (Rail), IMDG / GGVSea (Sea)).

14.1 UN-Number

UN 1910

14.2 UN proper shipping name

Calcium oxide

14.3 Transport hazard class(es)

Class 8

Calcium oxide is listed in IMDG (Amendment 34-08).

14.4 Packing group

Group III (Air transport (ICAO/IATA))

14.5 Environmental hazards

None

14.6 Special precautions for user

Avoid any release of dust during transportation, by using air-tight tanks for powders and covered trucks for pebbles.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not regulated.

15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance

Authorisations: Not required

Restrictions on use: None

Other EU regulations: Calcium oxide is not a SEVESO substance, not an ozone depleting substance and not a persistent organic pollutant.

National regulations: Water endangering class 1 (Germany)

15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

16 OTHER INFORMATION

Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.

16.1 Hazard Statements

- H315: Causes skin irritation
- H318: Causes serious eye damage
- H335: May cause respiratory irritation

16.2 Precautionary Statements

- P102: Keep out of reach of children
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P305+P351: IF IN EYES: Rinse cautiously with water for several minutes
- P310: Immediately call a POISON CENTRE or doctor/physician
- P302+P352: IF ON SKIN: Wash with plenty of soap and water
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P501: Dispose of contents/container in accordance with local/regional/national/international regulation FOR 2004-06-01 nr. 930: Forskrift om gjenvinning og behandling av avfall (avfallsforskriften) Kap 11. Inkludert den europeiske avfallslisten. Avfall fra letting, utvinning og i steinbrudd og fysisk og kjemisk behandling av mineraler: EAL- kode 010407, 010305

16.3 Abbreviations

- EC₅₀: median effective concentration
- LC₅₀: median lethal concentration
- LD₅₀: median lethal dose
- NOEC: no observable effect concentration
- OEL: occupational exposure limit
- PBT: persistent, bioaccumulative, toxic chemical
- PNEC: predicted no-effect concentration
- STEL: short-term exposure limit
- TWA: time weighted average
- vPvB: very persistent, very bioaccumulative chemical

16.4 Key literature references

Anonymous, 2006: Tolerable upper intake levels for vitamins and minerals Scientific Committee on Food, European Food Safety Authority, ISBN: 92-9199-014-0 [SCF document]



PRODUCT SAFETY DATA SHEET for QL-100-AF

prepared in accordance with Annex II of the REACH Regulation EC
1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010
last/ consolidated version (01.03.2022)



FRANZEF OSS
MINERALS

Version: 8.0/EN

Revision date: Aug./ 2022

Printing Date: August 12, 2022

Anonymous, 2008: Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL) for calcium oxide (CaO) and calcium dihydroxide (Ca(OH)₂), European Commission, DG Employment, Social Affairs and Equal Opportunities, SCOEL/SUM/137 February 2008

16.5 Revision

Section 1.3 details of the supplier of the safety data sheet is changed.

Disclaimer

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions.

ANNEX

Addition of exposure Scenarios (ES): ES 9.1-9.16, you will find the attachment of the ES on www.kalk.no under HMS.

End of the Safety Data Sheet